

## Commands:

-----

```
postfix start    start the damn thing
postfix stop     stop the whole ambaradam
postfix reload   for changes to take effect
```

## Places:

-----

```
/etc/postfix      configuration files
/usr/libexec/postfix daemons
/usr/sbin         commands
/var/log/maillog  logs
/var/spool/postfix queue files

/var/log/mail.err  errors (activities blocked)
/var/log/mail.warn warnings (activities continue)
/var/log/mail.info general activities
/var/log/mail.log
```

## main.cf configuration

-----

```
myhostname      Postfix system host name
mydomain        local domain name
myorigin        mail address in the from: field
mynetworks      remote trusted clients
mydestination    list of addresses Postfix is authorized to receive mail for
```

```
use SMTP authentication
use SASL protocol for SMTP authentication
```

## Sendmail header fields:

-----

```
address: implicit at first line after flags;
subject: next line after address;
content: next line after subject;
. (dot): end of message.
```

## Canonical domains (domain of the machine Postfix runs on)

-----

```
hostname: tecnorma;
IP addr: 192.168.2.74.
```

there are not hosted (other than tecnorma) nor relay (domains on other machines) domains on this machine.

This machine receives mail only for itself, as specified by directive mydestination; this machine receives mail only for addresses specified in /etc/postfix/virtual, and delivers them to accounts specified therein; accounts are created under /home, and each account is composed of several subfolders .

Mail clients on PCs connect to these accounts and see folders structure therein.